

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Identification of the substance or preparation

Cera Tec 300ml

Art.: 3721

Use of the substance/preparation

Protection against wear

Company/undertaking identification

LIQUI MOLY GmbH, Jerg-Wieland-Straße 4, D-89081 Ulm-Lehr
Telephone (+49) 0731-1420-0, Fax (+49) 0731-1420-88

E-mail address of the competent person: info@chemical-check.de, k.schnurbusch@chemical-check.de

Emergency telephone

Advisory office in case of poisoning:

Tel.:

Telephone number of the company in case of emergencies:

Tel. (+49) 0731-1420-0

2. HAZARDS IDENTIFICATION

Preparation is classified as hazardous in the sense of directive 1999/45/EC.

To people

See point 11 and 15.

Not applicable

To the environment

See point 12.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Product can compose a film on the water surface, which can prevent oxygen exchange.

Hazardous to drinking water, on escape of even small quantities.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	Symbol	R-phrases	EINECS, ELINCS
content %	Registration number (ECHA)		
Substituted ammonium molybdate			
2,5 -< 5	C/N	34-50-53	

For complete wording of the R-phrases, refer to point 16.

4. FIRST AID MEASURES

4.1 Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

4.2 Eye contact

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision: 03.11.2009 Replaces the version of: 02.10.2009 PDF date: 03.11.2009
Cera Tec 300ml Art.: 3721

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

4.3 Skin contact

Wash thoroughly with soap and copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.

4.4 Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.5 Special resources necessary for first aid

n.c.

5. FIRE-FIGHTING MEASURES

5.1 Suitable extinguishing media

CO₂

Dry extinguisher

Foam

Cool container at risk with water.

5.2 Extinguishing media which shall not be used for safety reasons

High volume water jet

5.3 Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Oxides of sulphur

Toxic pyrolysis products.

5.4 Special protective equipment for fire-fighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary

5.5 Further information

Dispose of contaminated extinction water according to official regulations.

6. ACCIDENTAL RELEASE MEASURES

Refer to point 13. and for personal protection refer to point 8.

6.1 Personal precautions

Ensure sufficient supply of air.

Avoid formation of oil mist.

Remove possible causes of ignition - do not smoke.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping

6.2 Environmental precautions

If leakage occurs, dam up.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

Avoid release to the environment.

6.3 Methods for cleaning up

Collect using absorbant material (e.g. Universal binding binder, sand, kieselguhr) and dispose of according to point 13.

Oil binder

7. HANDLING AND STORAGE

7.1 Handling

Tips for safe handling:

See point 6.1

Ensure good ventilation.

3 / 6
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision: 03.11.2009 Replaces the version of: 02.10.2009 PDF date: 03.11.2009
 Cera Tec 300ml Art.: 3721

Avoid formation of oil mist.
 Avoid contact with eyes or skin.
 Do not carry cleaning cloths soaked in product in trouser pockets.
 Do not heat to temperatures close to flash point.
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
 Observe directions on label and instructions for use.

7.2. Storage

Requirements for storage rooms and containers:

Store product closed and only in original packing.
 Not to be stored in gangways or stair wells.
 Solvent resistant floor
 Do not store with oxidizing agents.

Special storage conditions:

See point 10
 Store in a well ventilated place.
 Protect from direct sunlight and warming.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Exposure limit values

Chemical Name	Oil mist, mineral	Content %:
WEL-TWA: 5 mg/m3 (ACGIH)	WEL-STEL: 10 mg/m3 (ACGIH)	---
BMGV: ---	Other information: ---	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls

8.2.1 Occupational exposure controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.
 General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Respiratory protection:
 Normally not necessary.
 With oil mist formation:
 Filter A2 P2 (EN 14387)
 Observe wearing time limitations for respiratory protection equipment.
 Hand protection:
 Protective gloves, oil resistant (EN 374)
 If applicable
 Protective nitrile gloves (EN 374)
 Protective Neopren gloves (EN 374).
 Protective hand cream recommended.
 Eye protection:
 Tight fitting protective goggles with side protection (EN 166).
 Skin protection:
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments)

Additional information on hand protection - No tests have been performed.
 Selection made for preparations according to the best available knowledge and information on the ingredients.
 Selection of materials derived from glove manufacturer's indications.
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
 Selection of a suitable glove depends not only on the material but also on other quality characteristics

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision: 03.11.2009 Replaces the version of: 02.10.2009 PDF date: 03.11.2009
 Cera Tec 300ml Art.: 3721

and varies from manufacturer to manufacturer.

In the case of preparations the resistance of glove materials cannot be calculated in advance so it has to be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.2 Environmental exposure controls

n.av.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Colour:	Orange
Odour:	Characteristic
pH-value undiluted:	n.a.
Boiling point/boiling range (°C):	Not specified
Melting point/melting range (°C):	Not detected
Flash point (°C):	> 100
Minimum limit of explosion:	Not detected
Maximum limit of explosion:	Not detected
Vapour pressure:	Not detected
Density (g/ml):	0,893 (20°C)
Water solubility:	Insoluble
Viscosity:	~ 250 mPas (20°C)

10. STABILITY AND REACTIVITY

Conditions to avoid

See point 7

Stable when handled and stored correctly.

Strong heat

Materials to avoid

See point 7

Avoid contact with strong oxidizing agents.

Avoid contact with strong acids.

Hazardous decomposition products

See point 5.3

No decomposition when used as directed.

11. TOXICOLOGICAL INFORMATION

Acute toxicity and immediate effects

Ingestion, LD50 rat oral (mg/kg):	n.av.
Inhalation, LC50 rat inhal.(mg/l/4h):	n.av.
Skin contact, LD50 rat dermal (mg/kg):	n.av.
Eye contact:	n.av.

Delayed and chronic effects

Sensitization:	n.c.
Carcinogenicity:	n.c.
Mutagenicity:	n.c.
Reproductive toxicity:	n.c.
Narcosis:	n.c.

Further information

The product was not tested.

Classification according to calculation procedure.

The following may occur:

- Irritation of the eyes
- Product removes fat.
- Drying of the skin.

12. ECOLOGICAL INFORMATION

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision: 03.11.2009 Replaces the version of: 02.10.2009 PDF date: 03.11.2009
 Cera Tec 300ml Art.: 3721

The product was not tested.	
Water hazard class (Germany):	2
Self classification:	Yes (VwVwS)
Persistence and degradability:	Not readily but inherent biodegradable.
Behaviour in sewage plants:	Isolate as much as possible with an oil separator.
According to the recipe, contains no AOX.	
Aquatic toxicity:	See point 2.
Ecological toxicity:	n.av.
Accumulation:	Concentration in organisms possible.

13. DISPOSAL CONSIDERATIONS

13.1. for the material / preparation / residue

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of.
 EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.
 Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2001/118/EC, 2001/119/EC, 2001/573/EC)
 13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

Pay attention to local and national official regulations
 Implement substance recycling.
 E.g. suitable incineration plant.

13.2 for contaminated packing material

See point 13.1



Pay attention to local and national official regulations
 Empty container completely.
 Uncontaminated packaging can be recycled.
 Dispose of packaging that cannot be cleaned in the same manner as the substance.

14. TRANSPORT INFORMATION



General statements

UN-Number: 3082

Road/Rail-transport (ADR/RID)

Class/packing group:	9/III		
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (SUBSTITUTED AMMONIUM MOLYBDATE)			
Classification code:	M6		
LQ:	7		
Tunnel restriction code:	E		

Transport by sea

IMDG-code:	9/III (class/packing group)	
EmS:	F-A, S-F	
Marine Pollutant:	Yes	
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (SUBSTITUTED AMMONIUM MOLYBDATE)		

Transport by air

IATA:	9-/III (class/secondary danger/packing group)	
Environmentally hazardous substance, liquid, n.o.s. (SUBSTITUTED AMMONIUM MOLYBDATE)		

Additional information:

Danger code and packing code on request.

15. REGULATORY INFORMATION

**Classification according to Dangerous Product Regulations incl. EC Directives
 (67/548/EEC and 1999/45/EC)**

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision: 03.11.2009 Replaces the version of: 02.10.2009 PDF date: 03.11.2009
Cera Tec 300ml Art.: 3721



Symbols: N

Indications of danger:

Dangerous for the environment

R-phrases:

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

S-phrases:

29/35 Do not empty into drains; dispose of this material and its container in a safe way.

61 Avoid release to the environment. Refer to special instructions/safety data sheets.

Additions: n.a.

Observe restrictions:

Yes

Observe restrictive guidelines 76/769/EEC, 1999/51/EC, 1999/77/EC

16. OTHER INFORMATION

These details refer to the product as it is delivered.

Storage class VCI (Germany):

10

Revised points:

2, 3, 8, 9, 11, 12, 14, 15, 16

The following phrases represent the prescribed R-phrases / H-phrases (GHS) for the ingredients (designated in point 3).

34 Causes burns.

50 Very toxic to aquatic organisms.

53 May cause long-term adverse effects in the aquatic environment.

Legend:

n.a. = not applicable / n.v., k.D.v. = n.av. = not available / n.g. = n.c. = not checked

WEL = Workplace Exposure Limit EH40, TWA = Long-term exposure limit (8-hour TWA (= time weighted average) reference period), STEL =

Short-term exposure limit (15-minute reference period) / BMGV = Biological monitoring guidance value EH40

AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany) / BGW = "Biologischer Grenzwert" (biological limit value, Germany)

VbF = Regulations for flammable liquids (Austria)

WGK = water hazard class (Germany) - WGK 3 = very hazardous, WGK 2 = hazardous, WGK 1 = slightly hazardous to water

VOC = Volatile organic compounds / AOX = Adsorbable organic halogen compounds

VwVwS = Administrative Order relating to substances hazardous to water (Germany)

The statements made here should describe the product with regard to the necessary safety precautions - they are

not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Wöbbeler Straße 2-4, D-32839 Steinheim, Tel.: +49 5233 94 17 0, +49 1805-

CHEMICAL / +49 180 52 43 642, Fax: +49 5233 94 17 90, +49 180 50 50 455

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.